

**1. PRODUCT IDENTIFICATION**

PRODUCT NAME: 6051

PRODUCT COLOR: Black, Black 17038, 27038, 37038  
Blue, Blue 25053, 35177  
NL Brown 30117  
Clear  
Gold 17043  
Gray, Gray 26622  
Green 34031, 34087, 34230  
NL Orange 12300  
NL Red 11136  
White, White 17875, 27875, 27925, 37858, 37875

RECOMMENDED USE: Coding and Marking

**Manufacturer/Supplier:**

American Coding & Marking Ink Co., Inc. 1-908-756-0373  
1220 North Avenue  
Plainfield, NJ 07062-1796  
USA

**Emergency Telephone Number:**

TRANSPORTATION: CHEMTREC : 1-800-424-9300 (North America)  
1-703-527-3887 (International)

**2. HAZARDS IDENTIFICATION****Emergency Overview:****GHS Classification:**

Flammable liquids	Category 3
Skin corrosion/irritation	Category 3
Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 3

**GHS label elements, including precautionary statements**

Pictogram

Signal Word **Warning****Hazard Statements**

H226	Flammable liquid and vapor
H316	Causes mild skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation

H336

May cause drowsiness or dizziness

**Precautionary Statements**

P210	Keep away from heat/sparks/open flames/hot surfaces. — No smoking
P233	Keep container tightly closed
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P243	Take precautionary measures against static discharge
P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P264	Wash skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area
P280	Wear protective gloves/protective clothing/eye protection/face protection
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P312	Call a POISON CENTER or doctor/physician if you feel unwell
P332+P313	If skin irritation occurs: Get medical advice/attention
P337+P313	If eye irritation persists: Get medical advice/attention
P370+P378	In case of fire: Use Water spray, CO2, dry chemical, or alcohol resistant foam to extinguish
P403+233	Store in a well-ventilated place. Keep container tightly closed
P501	Dispose of contents/container to an approved waste disposal plant

**3. COMPOSITION AND INFORMATION ON INGREDIENTS**

Chemical Name	CAS No	Weight-%
1-Methoxy-2-propanol	107-98-2	5-15
Methyl Isobutyl Ketone	108-10-1	5-15
Xylene (mixed isomers)	1330-20-7	5-15
Ethylbenzene	100-41-4	0-5

**4. FIRST AID MEASURES****First Aid Measures****Ingestion:**

If swallowed, do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

**Eyes:**

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

**Skin:**

Wash off with soap and plenty of water. Consult a physician.

**Inhalation:** If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

**Most important symptoms and effects**

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

**Indication of any immediate medical attention and special treatment needed**

**Notes to Physician** Treat symptomatically

**5. FIREFIGHTING MEASURES****Suitable extinguishing media:**

Water fog, Multipurpose foam, Dry chemical, CO<sub>2</sub>

**Unsuitable extinguishing media:**

Do not use a solid water stream as it may scatter and spread fire.

**Specific hazards in case of fire:**

Fight as volatile liquid fire  
Water spray may spread fire.  
Flashback fires may occur  
Vapors are dense and may travel to remote ignition source

**Hazardous combustion products:**

Carbon oxides, nitrogen oxides, organic combustion products which may be toxic and/or irritating

**Protective equipment and precautions for fire fighters:**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**6. ACCIDENTAL RELEASE MEASURES****Personal precautions:**

Wear chemical goggles, gloves, boots and protective clothing. Wear respirator if necessary. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition and heat.

**Environmental precaution:**

Prevent additional discharge of material. Prevent material from entering sewers or water courses.

**Methods and materials for containment and cleaning up:**

Absorb small spills with sand, filter-aid, vermiculite or other inert absorbent material, then place in a chemical waste container. For large spills, contain with sand or earth dikes. Dispose of waste in accordance with applicable government regulations.

**7. HANDLING AND STORAGE**

**Precautions for safe handling:**

Avoid contact with eyes. Wash face, hands, and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing and eye/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Unscrew all caps slowly. Do not unscrew entirely until all pressure has been completely released. Keep away from heat/sparks/open flames/hot surfaces. Emptied containers may retain residues. Precautions apply to emptied containers.

**Conditions for safe storage, including incompatibilities:**

Keep container tightly closed and store in a cool, dry and well-ventilated place. Keep storage temperature between 4-32 °C (40-90 °F). Incompatible with strong oxidizing agents, strong acids, strong bases, alkali metals and halogens.

**8. EXPOSURE CONTROLS AND PERSONAL PROTECTION****Exposure Guidelines:**

Chemical Name and CAS#	ACGIH TLV	OSHA PEL	NIOSH IDLH
1-Methoxy-2-propanol 107-98-2	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 360 mg/m <sup>3</sup> STEL: 150 ppm STEL: 540 mg/m <sup>3</sup>	TWA: 100 ppm TWA: 360 mg/m <sup>3</sup> STEL: 150 ppm STEL: 540 mg/m <sup>3</sup>
Methyl Isobutyl Ketone 108-10-1	STEL: 75 ppm TWA: 25 ppm	TWA: 100 ppm TWA: 410 mg/m <sup>3</sup>	IDLH: 500 ppm TWA: 50 ppm TWA: 205 mg/m <sup>3</sup> STEL: 75 ppm STEL: 300 mg/m <sup>3</sup>
Xylene (mixed isomers) 1330-20-7	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 150 ppm STEL: 655 mg/m <sup>3</sup>	No Data
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>

**Appropriate engineering controls**

Apply technical measures to comply with the occupational exposure limits. Local exhaust and mechanical ventilations are recommended to be used as engineering controls.

**Individual protection measures, such as personal protective equipment:**

**Eye/Face protection:** Safety glasses with side shields or chemical goggles must be worn.

**Skin/Body protection:** Wear protective gloves. Wear suitable protective clothing and footwear appropriate for the risk of exposure.

**Respiratory protection:** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations.

**General hygiene:** Handle in accordance with good industrial hygiene and safety practice.

**SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES**

<u>Property</u>	<u>Values</u>	<u>Remarks-Methods</u>
Physical state:	Liquid	
Odor:	Characteristic	
Odor threshold:	Not determined	
pH:	Not determined	
Melting point/freezing point:	Not determined	
Boiling point/Boiling range:	Not determined	
Flash point:	24.4 °C / 76 °F	Tag Closed Cup
Evaporation Rate:	<1	butyl acetate = 1
Flammability (solid, gas):	Not determined	
Upper/lower flammability limits:	Not determined	
Vapor pressure:	Not determined	
Vapor density:	>1	air = 1
Specific gravity:	1.27	water = 1
Water solubility:	Slight	
Solubility in other solvents:	Not determined	
Partition Coefficient:	Not determined	
Auto-ignition Temperature:	Not determined	
Decomposition temperature:	Not determined	
Viscosity:	Not determined	
VOC Content (%):	25-30%	
VOC Content:	2.6-3.2 lbs/gal	

## 10. STABILITY AND REACTIVITY

**Reactivity:**

Not reactive under normal conditions.

**Chemical Stability:**

Stable under recommended storage conditions.

**Possibility of hazardous reactions:**

None under normal processing.

**Conditions to avoid:**

Keep out of reach of children. Keep away from heat, sparks and open flame. Keep away from contact with incompatible materials.

**Incompatible materials:**

Strong oxidizing agents, strong acids, strong bases, alkali metals, halogens

**Hazardous decomposition products:**

Carbon oxides, nitrogen oxides, thermal decomposition can lead to release of irritating and toxic gases and vapors.

## 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure**

**Eye contact:** Causes serious eye irritation

**Skin contact:** Causes skin irritation

**Inhalation:** Harmful if inhaled.

# SAFETY DATA SHEET

SDS# 6051-01

Revision Date: 8/20/2015

**Ingestion:** May be harmful if swallowed

## Component Information:

Chemical Name and CAS#	Oral LD50	Dermal LD50	Inhalation LC50
1-Methoxy-2-propanol 107-98-2	= 4,016 mg/kg ( Rat )	> 2,000 mg/kg ( Rabbit )	= 25.8 mg/ L ( Rat ) 6h
Methyl Isobutyl Ketone 108-10-1	= 2,080 mg/kg ( Rat )	>10 ml/kg ( Rabbit )	2000-4000 ppm ( Rat ) 4 h
Xylene (mixed isomers) 1330-20-7	= 3,523 mg/kg ( Rat )	> 4,200 mg/kg ( Rabbit )	> 20 mg/ L ( Rat ) 4h
Ethylbenzene 100-41-4	= 3,500 mg/kg ( Rat )	No data available	= 17.8 mg/ L ( Rat ) 4h

## Information on physical, chemical and toxicological effects:

**Symptoms** Please see section 4 of this SDS for symptoms

## Delayed and immediate effects as well as chronic effects from short and long-term exposure:

### Carcinogenicity:

Chemical Name	ACGIH	IARC	NTP	OSHA
Methyl Isobutyl Ketone		2B		
Ethylbenzene		2B		

### Legend

**ACGIH** (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

**IARC** (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Limited evidence of carcinogenicity

**NTP** (National Toxicology Program)

Known - Known Carcinogen

**OSHA** (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

## Numerical measures of toxicity:

Not determined

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity:

#### Component Information

Chemical Name and CAS#	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
1-Methoxy-2-propanol 107-98-2	No data available	LC50 - Pimephales promelas - 20,800 mg/L - 96h	No data available	EC50 - Daphnia magna - 23,300 mg/L - 48h
Methyl Isobutyl Ketone 108-10-1	No data available	LC50 - golden orfe - 675- 750 mg/L - 48h	No data available	EC50 - Daphnia magna - 4,300 mg/L - 24h
Xylene (mixed isomers) 1330-20-7	ErC50 - Pseudokirchneriella subcapitata - 4.36 mg.L - 73h	LC50 - Oncorhynchus mykiss - 2.6 mg/L - 96h	No data available	EC50 - Daphnia magna - 1 mg/L - 24h
Ethylbenzene 100-41-4	No data available	No data available	No data available	No data available

## Persistence/Degradability:

Not determined

## Bioaccumulation:

Not determined

**Mobility:**

Not determined

**Other Adverse Effects:**

Toxic to aquatic life.

**13. DISPOSAL CONSIDERATIONS****Disposal of Wastes:**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated Packaging:**

Dispose of as unused product in accordance with applicable regional, national and local laws and regulations.

**SECTION 14 – TRANSPORTATION INFORMATION****DOT**

UN number	1210
Proper shipping name	PRINTING INK
Hazard class	3
Packing group	III
ERG#	129

**IATA**

UN number	1210
Proper shipping name	PRINTING INK
Hazard class	3
Packing group	III

**IMDG**

UN number	1210
Proper shipping name	PRINTING INK
Hazard class	3
Packing group	III
Marine pollutant	No

**SECTION 15 – REGULATORY INFORMATION****TSCA STATUS:**

All Components listed

**OTHER REGULATORY:**

<u>Ingredient(s)</u>	<u>SARA 302</u>	<u>SARA 311/312</u>	<u>SARA 313</u>	<u>RECRA</u>	<u>CERCLA</u>
1-Methoxy-2-propanol	No	F, A	No	No	No
Methyl Isobutyl Ketone	No	F, A	Yes	U161	Yes
Xylene (mixed isomers)	No	F, A, C	Yes	U239	Yes
Ethylbenzene	No	F, A, C	Yes	No	Yes

**SARA 311/312 Codes:**

R = Reactive Hazard  
P = Pressure Hazard  
F = Fire Hazard  
A = Immediate/Acute

C = Delayed/Chronic

**California Prop. 65 Components:** Chemicals known to the state of California to cause birth defects or other reproductive harm:

Methyl Isobutyl Ketone  
Ethylbenzene

**SECTION 16 – OTHER INFORMATION**

HMIS:

Health:	2
Chronic Health Hazard	*
Flammability:	3
Reactivity:	0

**Revision Date:** 20-Aug-2015

**Replaces:** 26-Jun-2015

**Revision Note:** Added new color shade in section 1.

**Prepared by:** Thomas Sweet, VP

**DISCLAIMER OF LIABILITY**

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of the material described in this MSDS. Information contained herein is given in good faith and believed to be true and accurate, but all statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material, or results to be obtained from the use thereof. All of the listed ingredients in this product that are considered to present a health hazard as defined in Appendix A of the OSHA "Hazard Communication" standard (29CFR 1910.1200) as listed in Section II. All of the information given, including ingredient identification, CAS Number, and quantity, is proprietary information, which has been provided in order to meet the objective of the "Hazard Communication" standard. Data provided here are typical and not intended for use as product specifications. This formulation information is confidential, and only to be disclosed in accordance with Federal and State safety and health regulations. Permission to disclose any ingredient information for any other purpose is neither given nor implied.



**1. PRODUCT IDENTIFICATION**

PRODUCT NAME: 6051 Catalyst

PRODUCT COLOR: Gloss, Semi-Gloss, Lusterless

RECOMMENDED USE: Coding, marking, stenciling

**Manufacturer/Supplier:**

American Coding & Marking Ink Co., Inc. 1-908-756-0373  
 1220 North Avenue  
 Plainfield, NJ 07062-1796  
 USA

**Emergency Telephone Number:**

TRANSPORTATION: CHEMTREC : 1-800-424-9300 (North America)  
 1-703-527-3887 (International)

**2. HAZARDS IDENTIFICATION****Emergency Overview:****GHS Classification:**

Flammable liquids	Category 2
Aspiration hazard	Category 1
Acute toxicity - Oral	Category 5
Acute toxicity - Inhalation	Category 4
Skin corrosion/irritation	Category 1B
Skin sensitization	Category 1B
Serious eye damage/eye irritation	Category 1
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Reproductive toxicity	Category 2
Acute aquatic toxicity	Category 3

**GHS label elements, including precautionary statements**

Pictogram

Signal Word **Danger**

Hazard Statements

H225	Highly flammable liquid and vapor
H303	May be harmful if swallowed
H304	May be fatal if swallowed and enters airways
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H402	Harmful to aquatic life

**Precautionary Statements**

P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P210	Keep away from heat/sparks/open flames/hot surfaces. — No smoking
P240	Ground/bond container and receiving equipment
P242	Use only non-sparking tools
P243	Take precautionary measures against static discharge
P260	Do not breathe dust/fume/gas/mist/vapors/spray
P264	Wash skin thoroughly after handling
P271	Use only outdoors or in a well-ventilated area
P273	Avoid release to the environment
P280	Wear protective gloves/protective clothing/eye protection/face protection
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+351+361	IF ON SKIN (or hair): Rinse continuously with water for several minutes. Remove/Take off immediately all contaminated clothing
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P305+351+338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308+P313	IF exposed or concerned: Get medical advice/attention
P312	Call a POISON CENTER or doctor/physician if you feel unwell
P363	Wash contaminated clothing before reuse
P370+P378	In case of fire: Use Water spray, CO2, dry chemical, or alcohol resistant foam to extinguish
P403+233	Store in a well-ventilated place. Keep container tightly closed
P501	Dispose of contents/container to an approved waste disposal plant

**3. COMPOSITION AND INFORMATION ON INGREDIENTS**

Chemical Name	CAS No	Weight-%
1-Butanol	71-36-3	15-30
1-methoxy-2-propanol	107-98-2	5-15
Toluene	108-88-3	5-15
2,4,6-Tris(dimethylaminomethyl)phenol	90-72-2	2-10
Diethylenetriamine	111-40-0	2-5

#### 4. FIRST AID MEASURES

##### First Aid Measures

- Ingestion:** If swallowed, do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.
- Eyes:** Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
- Skin:** Wash off with soap and plenty of water. Consult a physician.
- Inhalation:** If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

##### Most important symptoms and effects

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

##### Indication of any immediate medical attention and special treatment needed

**Notes to Physician**      Treat symptomatically

#### 5. FIREFIGHTING MEASURES

##### Suitable extinguishing media:

Water fog, Multipurpose foam, Dry chemical, CO<sub>2</sub>

##### Specific hazards in case of fire:

Fight as volatile liquid fire

##### Hazardous combustion products:

Carbon oxides, Nitrogen oxides, ammonia

##### Protective equipment and precautions for fire fighters:

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

#### 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions:**

Wear chemical goggles, gloves, boots and protective clothing. Wear respirator if necessary. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition and heat.

**Environmental precaution:**

Prevent additional discharge of material. Prevent material from entering sewers or water courses.

**Methods and materials for containment and cleaning up:**

Absorb small spills with sand, filter-aid, vermiculite or other inert absorbent material, then place in a chemical waste container. For large spills, contain with sand or earth dikes. Dispose of waste in accordance with applicable government regulations.

## 7. HANDLING AND STORAGE

**Precautions for safe handling:**

Avoid contact with eyes. Wash face, hands, and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing and eye/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Unscrew all caps slowly. Do not unscrew entirely until all pressure has been completely released. Keep away from heat/sparks/open flames/hot surfaces. Emptied containers may retain residues. Precautions apply to emptied containers.

**Conditions for safe storage, including incompatibilities:**

Keep container tightly closed and store in a cool, dry and well-ventilated place. Keep storage temperature between 4-32 °C (40-90 °F). Incompatible with strong oxidizing agents, strong acids, strong bases, alkali metals and halogens.

## 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

**Exposure Guidelines:**

Chemical Name and CAS#	ACGIH TLV	OSHA PEL	NIOSH IDLH
1-Butanol CAS 71-36-3	TWA: 20 ppm	TWA: 100 ppm TWA: 300 mg/m <sup>3</sup> (skin)	IDLH: 1400 ppm TWA: 50 ppm TWA: 150 mg/m <sup>3</sup> (skin)
1-methoxy-2-propanol CAS 107-98-2	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 360 mg/m <sup>3</sup> STEL: 150 ppm STEL: 540 mg/m <sup>3</sup>	TWA: 100 ppm TWA: 360 mg/m <sup>3</sup> STEL: 150 ppm STEL: 540 mg/m <sup>3</sup>
Toluene CAS 108-88-3	TWA: 20 ppm	TWA: 100 ppm TWA: 375 mg/m <sup>3</sup> STEL: 150 ppm STEL: 560 mg/m <sup>3</sup>	TWA: 100 ppm TWA: 375 mg/m <sup>3</sup> STEL: 150 ppm STEL: 560 mg/m <sup>3</sup>
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	Not established	Not established	Not established
Diethylenetriamine CAS 111-40-0	Not Established	Not Established	TWA: 1 ppm TWA: 4 mg/m <sup>3</sup> (skin)

**Appropriate engineering controls**

Apply technical measures to comply with the occupational exposure limits. Local exhaust and mechanical ventilations are recommended to be used as engineering controls.

**Individual protection measures, such as personal protective equipment:**

- Eye/Face protection:** Safety glasses with side shields or chemical goggles must be worn.
- Skin/Body protection:** Wear protective gloves. Wear suitable protective clothing and footwear appropriate for the risk of exposure.
- Respiratory protection:** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations.
- General hygiene:** Handle in accordance with good industrial hygiene and safety practice.

**SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES**

<u>Property</u>	<u>Values</u>	<u>Remarks-Methods</u>
Physical state:	Liquid	
Odor:	Solvent	
Odor threshold:	Not determined	
pH:	Not determined	
Melting point/freezing point:	Not determined	
Boiling point/Boiling range:	Not determined	
Flash point:	18.9 °C / 66 °F	Tag Closed Cup
Evaporation Rate:	<1	butyl acetate = 1
Flammability (solid, gas):	Not determined	
Upper/lower flammability limits:	Not determined	
Vapor pressure:	Not determined	
Vapor density:	>1	air = 1
Specific gravity:	1.0	water = 1
Water solubility:	Not soluble	
Solubility in other solvents:	Not determined	
Partition Coefficient:	Not determined	
Auto-ignition Temperature:	Not determined	
Decomposition temperature:	Not determined	
Viscosity:	Not determined	
VOC Content (%):	40%	
VOC Content:	3.3 lbs/gal	

**10. STABILITY AND REACTIVITY****Reactivity:**

No Data.

**Chemical Stability:**

Stable under recommended storage conditions.

**Possibility of hazardous reactions:**

Reacts with oxidizing agents. Reacts with strong acids.

**Conditions to avoid:**

Keep out of reach of children. Keep away from heat, sparks and open flame. Keep away from contact with incompatible materials.

**Incompatible materials:**

Strong oxidizing agents, strong acids, strong bases, alkali metals

**Hazardous decomposition products:**

Carbon oxides, nitrogen oxides, thermal decomposition can lead to release of irritating and toxic gases and vapors

**11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

<b>Eye contact:</b>	Causes serious eye damage
<b>Skin contact:</b>	Corrosive. Can cause chemical burns
<b>Inhalation:</b>	Causes respiratory tract irritation. May cause drowsiness, dizziness, headache and nausea.
<b>Ingestion:</b>	May be harmful if swallowed

**Component Information:**

Chemical Name and CAS#	Oral LD50	Dermal LD50	Inhalation LC50
1-Butanol CAS 71-36-3	= 790 mg/kg ( Rat )	= 5,620 mg/kg ( Rabbit )	> 17.9 mg/L ( Rat ) 4 h
1-methoxy-2-propanol CAS 107-98-2	= 4,016 mg/kg ( Rat )	> 2,000 mg/kg ( Rabbit )	= 25.8 mg/L ( Rat ) 6 h
Toluene CAS 108-88-3	= 5,580 mg/kg ( Rat )	> 5000 mg/kg ( Rabbit )	= 28.1 mg/L ( Rat ) 4 h
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	= 2,169 mg/kg ( Rat )	No data	No data
Diethylenetriamine CAS 111-40-0	= 819 – 1430 mg/kg ( Rat )	= 950 – 1240 mg/kg ( Rabbit )	= 1.8 mg/L ( Rat ) 4 h

**Information on physical, chemical and toxicological effects:**

**Symptoms** Please see section 4 of this SDS for symptoms

**Delayed and immediate effects as well as chronic effects from short and long-term exposure:**

**Carcinogenicity:** No ingredient is listed as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
None				

**Legend**

**ACGIH (American Conference of Governmental Industrial Hygienists)**

A3 - Animal Carcinogen

**IARC (International Agency for Research on Cancer)**

Group 1 - Carcinogenic to Humans

**NTP (National Toxicology Program)**

Known - Known Carcinogen

**OSHA (Occupational Safety and Health Administration of the US Department of Labor)**

X - Present

**Numerical measures of toxicity:**

Not determined

**12. ECOLOGICAL INFORMATION****Ecotoxicity:**

**Component Information**

Chemical Name and CAS#	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
1-Butanol CAS 71-36-3	No Data	LC50 – Pimephales promelas – 1376 mg/L – 96h	No Data	EC50 – Daphnia magna – 1328 mg/L – 48h
1-methoxy-2-propanol CAS 107-98-2	No Data	No Data	No Data	No Data
Toluene CAS 108-88-3	No Data	LC50 – Oncorhynchus mykiss – 75.5 mg/L – 96h	No Data	EC50 – Ceriodaphnia dubia – 3.78 mg/L – 48h
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	EC50 – Scenedesmus subspicatus – 84 mg/L – 72h	LC50 – Cyprinus carpio – 175 mg/L – 96h		
Diethylenetriamine CAS 111-40-0	EC50 – Scenedesmus subspicatus – 592 mg/L – 96h	LC50 – Leuciscus idus – 430 mg/L – 96h	No Data	EC50 – Daphnia magna – 17 mg/L – 48h

**Persistence/Degradability:**

Not determined

**Bioaccumulation:**

Not determined

**Mobility:**

Not determined

**Other Adverse Effects:**

No data available

**13. DISPOSAL CONSIDERATIONS****Disposal of Wastes:**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated Packaging:**

Dispose of as unused product in accordance with applicable regional, national and local laws and regulations.

**SECTION 14 – TRANSPORTATION INFORMATION****DOT**

**UN number** 1210  
**Proper shipping name** Printing Ink  
**Hazard class** 3  
**Packing group** II  
**ERG#** 129

**IATA**

**UN number** 1210  
**Proper shipping name** Printing Ink  
**Hazard class** 3  
**Packing group** II

**IMDG**

**UN number** 1210

**Proper shipping name** Printing Ink  
**Hazard class** 3  
**Packing group** II  
**Marine pollutant** No

**SECTION 15 – REGULATORY INFORMATION**

TSCA STATUS: All Components listed

OTHER REGULATORY:

<u>Ingredient(s)</u>	<u>SARA 302</u>	<u>SARA 311/312</u>	<u>SARA 313</u>	<u>RECRA</u>	<u>CERCLA</u>
1-Butanol	No	F, A, C	Yes	U031	No
1-methoxy-2-propanol	No	F, A	No	No	No
Toluene	No	F, A, C	Yes	U220	Yes
Diethylenetriamine	No	F, A	No	No	No

SARA 311/312 Codes: R = Reactive Hazard  
P = Pressure Hazard  
F = Fire Hazard  
A = Immediate/Acute  
C = Delayed/Chronic

**California Proposition 65 Components:** Chemicals known to the state of California to cause birth defects or other reproductive harm:

Toluene CAS# 108-88-3

**SECTION 16 – OTHER INFORMATION**

HMIS:

Health: 3  
Chronic Health Hazard \*  
Flammability: 3  
Reactivity: 1

**Revision Date:** 20-Aug-2015  
**Replaces:** 18-Jun-2015  
**Revision Note:** Change to section 15

**Prepared by:** Thomas Sweet, VP

**DISCLAIMER OF LIABILITY**

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of the material described in this MSDS. Information contained herein is given in good faith and believed to be true and accurate, but all statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material, or results to be



obtained from the use thereof. All of the listed ingredients in this product that are considered to present a health hazard as defined in Appendix A of the OSHA "Hazard Communication" standard (29CFR 1910.1200) as listed in Section II. All of the information given, including ingredient identification, CAS Number, and quantity, is proprietary information, which has been provided in order to meet the objective of the "Hazard Communication" standard. Data provided here are typical and not intended for use as product specifications. This formulation information is confidential, and only to be disclosed in accordance with Federal and State safety and health regulations. Permission to disclose any ingredient information for any other purpose is neither given nor implied.