


## 1. Identification

Product identifier	Markers, GPX Classic (All Colors except silver)	
Other means of identification	None.	
Recommended use	Marking.	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/Distributor information		
Company name	Diagraph Marking & Coding	
Address	5307 Meadowland Parkway Marion IL 62959	
Telephone	1-800-521-3047	
E-mail	msds@diagraphmsp.com	
Contact person	Customer Service	
Emergency phone number	Emergency telephone	800-535-5053 (US only) +1-352-323-3500 international

## 2. Hazard(s) identification

<b>Physical hazards</b>	Flammable liquids	Category 3
<b>Health hazards</b>	Acute toxicity, dermal	Category 4
	Acute toxicity, inhalation	Category 4
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2
	Carcinogenicity	Category 2
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2 (Central nervous system, Liver, Kidney)
	Aspiration hazard	Category 1
<b>Environmental hazards</b>	Hazardous to the aquatic environment, acute hazard	Category 2
<b>OSHA defined hazards</b>	Not classified.	
<b>Label elements</b>		

<b>Signal word</b>	Danger
<b>Hazard statement</b>	Flammable liquid and vapor. May be fatal if swallowed and enters airways. Harmful in contact with skin. Causes skin irritation. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. Toxic to aquatic life.
<b>Precautionary statement</b>	
<b>Prevention</b>	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment.

<b>Response</b>	If exposed or concerned: Get medical advice/attention. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.
<b>Storage</b>	Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
<b>Disposal</b>	Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Hazard(s) not otherwise classified (HNOC)</b>	None known.
<b>Supplemental information</b>	None.

### 3. Composition/information on ingredients

#### Mixtures

Chemical name	CAS number	%
Xylene (mix)	1330-20-7	40-80
Titanium dioxide	13463-67-7	0-30
Ethylbenzene	100-41-4	5-20
1-Methoxy-2-propanol	107-98-2	0-20
Carbon black	1333-86-4	0-10
Kaolin, calcined	92704-41-1	0-10
2-Methoxy-1-methylethyl acetate	108-65-6	0-5
1-Propanol	71-23-8	0-2.9
Cumene	98-82-8	0.4 - 0.8
Toluene	108-88-3	<0.2

<b>Composition comments</b>	All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.
-----------------------------	--

### 4. First-aid measures

<b>Inhalation</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a POISON CENTER or doctor/physician if you feel unwell.
<b>Skin contact</b>	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
<b>Most important symptoms/effects, acute and delayed</b>	Abdominal pain. Decrease in motor functions. Behavioral changes. Narcosis. Nausea, vomiting. Headache. May cause drowsiness and dizziness. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. Edema. Jaundice. Prolonged exposure may cause chronic effects.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

## 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO <sub>2</sub> ).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	Flammable liquid and vapor.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	<p>Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent product from entering drains.</p> <p>Large Spills: Stop the flow of material, if this is without risk. A vapor-suppressing foam may be used to reduce vapors. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.</p> <p>Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.</p>
<b>Environmental precautions</b>	<p>Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.</p> <p>Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.</p>

## 7. Handling and storage

<b>Precautions for safe handling</b>	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.
<b>Conditions for safe storage, including any incompatibilities</b>	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
1-Propanol (CAS 71-23-8)	PEL	500 mg/m <sup>3</sup> 200 ppm	

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value	Form
Carbon black (CAS 1333-86-4)	PEL	3.5 mg/m3	
Cumene (CAS 98-82-8)	PEL	245 mg/m3 50 ppm	
Ethylbenzene (CAS 100-41-4)	PEL	435 mg/m3 100 ppm	
Titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
Xylene (mix) (CAS 1330-20-7)	PEL	435 mg/m3 100 ppm	

**US. OSHA Table Z-2 (29 CFR 1910.1000)**

Components	Type	Value	
Toluene (CAS 108-88-3)	Ceiling	300 ppm	
	TWA	200 ppm	

**US. OSHA Table Z-3 (29 CFR 1910.1000)**

Components	Type	Value	Form
Titanium dioxide (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.

**US. ACGIH Threshold Limit Values**

Components	Type	Value	Form
1-Methoxy-2-propanol (CAS 107-98-2)	STEL	100 ppm	
	TWA	50 ppm	
1-Propanol (CAS 71-23-8)	TWA	100 ppm	
Carbon black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.
Cumene (CAS 98-82-8)	TWA	50 ppm	
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm	
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
Toluene (CAS 108-88-3)	TWA	20 ppm	
Xylene (mix) (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value	
1-Methoxy-2-propanol (CAS 107-98-2)	STEL	540 mg/m3	
		150 ppm	
	TWA	360 mg/m3 100 ppm	
1-Propanol (CAS 71-23-8)	STEL	625 mg/m3 250 ppm	
	TWA	500 mg/m3 200 ppm	
Carbon black (CAS 1333-86-4)	TWA	3.5 mg/m3	
Cumene (CAS 98-82-8)	TWA	245 mg/m3 50 ppm	

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value
Ethylbenzene (CAS 100-41-4)	STEL	545 mg/m3
		125 ppm
	TWA	435 mg/m3 100 ppm
Toluene (CAS 108-88-3)	STEL	560 mg/m3
		150 ppm
	TWA	375 mg/m3 100 ppm

**Biological limit values****ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Ethylbenzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*
Xylene (mix) (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Exposure guidelines****US - California OELs: Skin designation**

1-Methoxy-2-propanol (CAS 107-98-2)	Can be absorbed through the skin.
1-Propanol (CAS 71-23-8)	Can be absorbed through the skin.
Cumene (CAS 98-82-8)	Can be absorbed through the skin.
Toluene (CAS 108-88-3)	Can be absorbed through the skin.

**US - Minnesota Haz Subs: Skin designation applies**

1-Propanol (CAS 71-23-8)	Skin designation applies.
Cumene (CAS 98-82-8)	Skin designation applies.
Toluene (CAS 108-88-3)	Skin designation applies.

**US - Tennessee OELs: Skin designation**

Cumene (CAS 98-82-8)	Can be absorbed through the skin.
----------------------	-----------------------------------

**US. NIOSH: Pocket Guide to Chemical Hazards**

1-Propanol (CAS 71-23-8)	Can be absorbed through the skin.
Cumene (CAS 98-82-8)	Can be absorbed through the skin.

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Cumene (CAS 98-82-8)	Can be absorbed through the skin.
----------------------	-----------------------------------

**Appropriate engineering controls**

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Chemical respirator with organic vapor cartridge and full facepiece. Wear safety glasses with side shields (or goggles) and a face shield.

**Skin protection**

**Hand protection** The following glove materials are recommended: Nitrile.  
Full contact: Use gloves classified protection index 3 with breakthrough time of 5 minutes.  
Minimum glove thickness 0.4 ± 0.05 mm.

**Other** Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

**Respiratory protection** Chemical respirator with organic vapor cartridge and full facepiece.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and chemical properties****Appearance**

<b>Physical state</b>	Liquid.
<b>Form</b>	Liquid.
<b>Color</b>	According to product specification.

**Odor** Characteristic.

**Odor threshold** Not available.

**pH** Not available.

**Melting point/freezing point** Not available.

**Initial boiling point and boiling range** 248 °F (120 °C)

**Flash point** 75.2 °F (24.0 °C)

**Evaporation rate** Not available.

**Flammability (solid, gas)** Not applicable.

**Upper/lower flammability or explosive limits**

**Flammability limit - lower (%)** 1 % v/v

**Flammability limit - upper (%)** 7.8 % v/v

**Explosive limit - lower (%)** Not available.

**Explosive limit - upper (%)** Not available.

**Vapor pressure** 9.5 hPa at 20°C.

**Vapor density** Not available.

**Relative density** Not available.

**Solubility(ies)**

**Solubility (water)** Fully miscible.

**Partition coefficient (n-octanol/water)** Not available.

**Auto-ignition temperature** Not available.

**Decomposition temperature** Not available.

**Viscosity** Not available.

**Other information**

**Explosive properties** Not explosive.

**Oxidizing properties** Not oxidizing.

**10. Stability and reactivity**

**Reactivity** The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions.

**Possibility of hazardous reactions** No dangerous reaction known under conditions of normal use.

**Conditions to avoid** Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

**Incompatible materials** Strong acids. Strong oxidizing agents. Halogens.

**Hazardous decomposition products** No hazardous decomposition products are known.

**11. Toxicological information****Information on likely routes of exposure**

**Inhalation** Harmful if inhaled. May cause damage to organs through prolonged or repeated exposure by inhalation. May cause irritation to the respiratory system. May cause drowsiness and dizziness.

<b>Skin contact</b>	Harmful in contact with skin. Causes skin irritation.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Ingestion</b>	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	Abdominal pain. Behavioral changes. Decrease in motor functions. Narcosis. Nausea, vomiting. Jaundice. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. May cause drowsiness and dizziness. Skin irritation. May cause redness and pain. Edema.

#### Information on toxicological effects

**Acute toxicity** Harmful if inhaled. Harmful in contact with skin. May be fatal if swallowed and enters airways.

Components	Species	Test Results
1-Methoxy-2-propanol (CAS 107-98-2)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Rabbit	13000 mg/kg
<b>Inhalation</b>		
LC50	Rat	>= 6 mg/l, 4 Hours
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg
Carbon black (CAS 1333-86-4)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Rabbit	> 3000 mg/kg
<b>Oral</b>		
LD50	Rat	> 8000 mg/kg
Cumene (CAS 98-82-8)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Rabbit	> 3160 mg/kg, 24 Hours
<b>Inhalation</b>		
LC50	Rat	8000 ppm, 4 Hours
<b>Oral</b>		
LD50	Rat	2910 mg/kg
Ethylbenzene (CAS 100-41-4)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Rabbit	15400 mg/kg
<b>Inhalation</b>		
LC50	Rat	17.4 mg/l, 4 hours
<b>Oral</b>		
LD50	Rat	3500 - 4700 mg/kg
Toluene (CAS 108-88-3)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Rabbit	12200 mg/kg
<b>Inhalation</b>		
Vapor		
LC50	Rat	28.1 mg/l, 4 Hours

Components	Species	Test Results
Xylene (mix) (CAS 1330-20-7)		
<u>Acute</u>		
Oral		
LD50	Rat	3523 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Suspected of causing cancer.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Carbon black (CAS 1333-86-4)	2B Possibly carcinogenic to humans.	
Cumene (CAS 98-82-8)	2B Possibly carcinogenic to humans.	
Ethylbenzene (CAS 100-41-4)	2B Possibly carcinogenic to humans.	
Titanium dioxide (CAS 13463-67-7)	2B Possibly carcinogenic to humans.	
Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.	
Xylene (mix) (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.	
NTP Report on Carcinogens		
Cumene (CAS 98-82-8)	Reasonably Anticipated to be a Human Carcinogen.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)		
Not regulated.		
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects. The product contains a small amount of substance that is suspected of damaging fertility or the unborn child.	
Specific target organ toxicity - single exposure	May cause respiratory irritation. May cause drowsiness and dizziness.	
Specific target organ toxicity - repeated exposure	May cause damage to organs (Central nervous system, Liver, Kidney) through prolonged or repeated exposure.	
Aspiration hazard	May be fatal if swallowed and enters airways.	
Chronic effects	May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.	
Further information	No data available.	

## 12. Ecological information

Ecotoxicity		Toxic to aquatic life.	
Components		Species	Test Results
Carbon black (CAS 1333-86-4)			
Aquatic			
Acute			
Fish	LC50	Leuciscus idus	>= 1000 mg/l, 96 Hours
Cumene (CAS 98-82-8)			
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.7 mg/l, 96 hours
Ethylbenzene (CAS 100-41-4)			
Aquatic			
Acute			
Crustacea	EC50	Water flea (Daphnia magna)	1.81 - 2.38 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4.2 mg/l, 96 hours



Components		Species	Test Results
<i>Chronic</i>			
Crustacea	EC50	Ceriodaphnia dubia	3.6 mg/l, 7 days
Toluene (CAS 108-88-3)			
<b>Aquatic</b>			
<i>Acute</i>			
Crustacea	EC50	Daphnia magna	11.5 mg/l, 48 hours
Fish	LC50	Oncorhynchus kisutch	5.5 mg/l, 96 hours
<i>Chronic</i>			
Crustacea	NOEC	Ceriodaphnia dubia	0.74 mg/l, 7 days
Fish	NOEC	Oncorhynchus kisutch	1.4 mg/l, 40 days
Xylene (mix) (CAS 1330-20-7)			
<b>Aquatic</b>			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.6 mg/l, 96 hours

**Persistence and degradability** No data is available on the degradability of this product.

#### Bioaccumulative potential

##### Partition coefficient n-octanol / water (log Kow)

Ethylbenzene (CAS 100-41-4)	3.15
Toluene (CAS 108-88-3)	2.73
Xylene (mix) (CAS 1330-20-7)	3.12 - 3.2

**Mobility in soil** No data available.

**Other adverse effects** The product contains volatile organic compounds which have a photochemical ozone creation potential.

### 13. Disposal considerations

<b>Disposal instructions</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

### 14. Transport information

#### DOT

<b>UN number</b>	UN1210
<b>UN proper shipping name</b>	Printing ink, flammable
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	3
<b>Packing group</b>	III
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Special provisions</b>	B1, IB3, T2, TP1
<b>Packaging exceptions</b>	150
<b>Packaging non bulk</b>	173
<b>Packaging bulk</b>	242

#### IATA

<b>UN number</b>	UN1210
<b>UN proper shipping name</b>	Printing ink

**Transport hazard class(es)**

**Class** 3  
**Subsidiary risk** -  
**Label(s)** 3

**Packing group** III  
**Environmental hazards** No  
**ERG Code** 3L

**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**IMDG**

**UN number** UN1210  
**UN proper shipping name** PRINTING INK

**Transport hazard class(es)**

**Class** 3  
**Subsidiary risk** -  
**Label(s)** 3

**Packing group** III  
**Environmental hazards**

**Marine pollutant** No

**EmS** F-E, S-D

**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not established.

**15. Regulatory information**

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Cumene (CAS 98-82-8)	Listed.
Ethylbenzene (CAS 100-41-4)	Listed.
Toluene (CAS 108-88-3)	Listed.
Xylene (mix) (CAS 1330-20-7)	Listed.

**SARA 304 Emergency release notification**

Not regulated.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)**

Not regulated.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)****SARA 302 Extremely hazardous substance**

Not listed.

**SARA 311/312 Hazardous chemical** Yes

**Classified hazard categories**

- Flammable (gases, aerosols, liquids, or solids)
- Acute toxicity (any route of exposure)
- Skin corrosion or irritation
- Serious eye damage or eye irritation
- Carcinogenicity
- Specific target organ toxicity (single or repeated exposure)
- Aspiration hazard

**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
Ethylbenzene	100-41-4	5-20
Xylene (mix)	1330-20-7	40-80

**Other federal regulations****Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Cumene (CAS 98-82-8)  
 Ethylbenzene (CAS 100-41-4)

Toluene (CAS 108-88-3)  
Xylene (mix) (CAS 1330-20-7)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Safe Drinking Water Act (SDWA)** Not regulated.

**Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number**

Toluene (CAS 108-88-3) 6594

**Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))**

Toluene (CAS 108-88-3) 35 %WV

**DEA Exempt Chemical Mixtures Code Number**

Toluene (CAS 108-88-3) 594

**FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace**

1-Propanol (CAS 71-23-8) Low priority

**US state regulations**

**US. Massachusetts RTK - Substance List**

1-Methoxy-2-propanol (CAS 107-98-2)  
1-Propanol (CAS 71-23-8)  
Carbon black (CAS 1333-86-4)  
Cumene (CAS 98-82-8)  
Ethylbenzene (CAS 100-41-4)  
Titanium dioxide (CAS 13463-67-7)  
Toluene (CAS 108-88-3)  
Xylene (mix) (CAS 1330-20-7)

**US. New Jersey Worker and Community Right-to-Know Act**

1-Methoxy-2-propanol (CAS 107-98-2)  
1-Propanol (CAS 71-23-8)  
Carbon black (CAS 1333-86-4)  
Cumene (CAS 98-82-8)  
Ethylbenzene (CAS 100-41-4)  
Titanium dioxide (CAS 13463-67-7)  
Toluene (CAS 108-88-3)  
Xylene (mix) (CAS 1330-20-7)

**US. Pennsylvania Worker and Community Right-to-Know Law**

1-Methoxy-2-propanol (CAS 107-98-2)  
1-Propanol (CAS 71-23-8)  
Carbon black (CAS 1333-86-4)  
Cumene (CAS 98-82-8)  
Ethylbenzene (CAS 100-41-4)  
Titanium dioxide (CAS 13463-67-7)  
Toluene (CAS 108-88-3)  
Xylene (mix) (CAS 1330-20-7)

**US. Rhode Island RTK**

1-Methoxy-2-propanol (CAS 107-98-2)  
1-Propanol (CAS 71-23-8)  
Carbon black (CAS 1333-86-4)  
Cumene (CAS 98-82-8)  
Ethylbenzene (CAS 100-41-4)  
Titanium dioxide (CAS 13463-67-7)  
Toluene (CAS 108-88-3)  
Xylene (mix) (CAS 1330-20-7)

**California Proposition 65**



**WARNING:** This product can expose you to chemicals including Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**California Proposition 65 - CRT: Listed date/Carcinogenic substance**

1,4-Dioxane (CAS 123-91-1)	Listed: January 1, 1988
Benzene (CAS 71-43-2)	Listed: February 27, 1987
Carbon black (CAS 1333-86-4)	Listed: February 21, 2003
Cumene (CAS 98-82-8)	Listed: April 6, 2010

Ethylbenzene (CAS 100-41-4)

Listed: June 11, 2004

Naphthalene (CAS 91-20-3)

Listed: April 19, 2002

Titanium dioxide (CAS 13463-67-7)

Listed: September 2, 2011

**California Proposition 65 - CRT: Listed date/Developmental toxin**

Benzene (CAS 71-43-2)

Listed: December 26, 1997

Toluene (CAS 108-88-3)

Listed: January 1, 1991

**California Proposition 65 - CRT: Listed date/Male reproductive toxin**

Benzene (CAS 71-43-2)

Listed: December 26, 1997

**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

1-Methoxy-2-propanol (CAS 107-98-2)

Carbon black (CAS 1333-86-4)

Cumene (CAS 98-82-8)

Ethylbenzene (CAS 100-41-4)

Titanium dioxide (CAS 13463-67-7)

Toluene (CAS 108-88-3)

Xylene (mix) (CAS 1330-20-7)

**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

**16. Other information, including date of preparation or last revision**

Issue date	19-April-2018
Revision date	-
Version #	01
HMIS® ratings	Health: 2* Flammability: 3 Physical hazard: 0

**NFPA ratings**



**Disclaimer**

Diagram Marking & Coding cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.