
# AMERICANMARKING, INC.

# **Technical Bulletin**





### **SPECIFICATIONS**

#### **HP-100NI Small Non-Indexing Model**

Print Area Approximately 2" x 6.5"
A: 8.4" (213 MM) B: Circumference = 6.5" (165 MM)
Net Weight - 1 LB. 11 OZ. (.77 KG)

#### **HP-200NI Large Non-Indexing Model**

Print Area Approximately 2" x 9"
A: 9.3" (236 MM) B: Circumference = 9.1" (231 MM)
Net Weight - 1 LB. 11 OZ. (.77 KG)

#### **HP-200 Large Indexing Model**

Print Area Approximately 2" x 9"
A: 9.3" (236 MM) B: Circumference = 9.1" (231 MM)
Net Weight - 1 LB. 10.5 OZ. (.74 KG)

## **Porous Hand Printer**

Universal's Hand Printers are designed to provide an efficient, manual method of printing date codes, product I.D.'s, lot numbers or other shipping & handling data. This lightweight hand coder is ideal for use in the shipping room or the warehouse where automatic coding is not possible.

Heavy duty construction includes an anodized aircraft aluminum frame, sealed ball bearings and an eccentric ink roller adjustment. Standard features include a dry Microcell reinkable roll and Universal's versatile Ribtype die fastening system. Ribtype die's make changing codes & other data quick and easy, minimizing costly down time.

These units are designed for use with Universal #1150 coder ink for marking on cardboard and other porous materials. A variety of other inks are available for special applications.

Non-indexing Hand Printers continuously print at repeat intervals equal to the drum circumference. The print drum on the indexing printer returns to the same start position after each rotation, allowing for accurate print registration.

Custom sizes are available for special applications.

Note: The porous Hand printer's are not recommended for regular usage with alcohol based inks.

#### **FEATURES**

- Lightweight anodized aircraft aluminum frame.
- Sealed ball bearings for smooth print drum rotation. (Non-indexing printers)
- Impact resistant plastic handle Extension handles are available.
- · Re-inkable Microcell roller.
- Eccentric adjustment for ink roll to die face contact.
- Universal Ribtype die system accommodates logo dies and individual characters.

Stock Printers are equipped with Universal's Ribtype Die System & Microcell Roll.

BIRMINGHAM CORPORATE OFFICE:

VOICE: 800.964.6275 FAX: 205.733.1720 americanmarking@aol.com AMERICANMARKING, INC.

2435 VALE DRIVE BIRMINGHAM, AL 35244 www.americanmarking.com CHATTANOOGA
REGIONAL SALES OFFICE:
VOICE: 800.685-6275

FAX: 423-843-0535
gary@americanmarking.com